

SPECIFICATIONS

Cells per Unit	6
Voltage per Unit	12
Capacity	130Ah@20hr-rate to 1.75V per cell@25°C
Weight	Approx. 33.0 Kg(Tolerance ± 3%)
Terminal	AP
Reference Capacity	C5 105.0AH C20 130.0AH
Float Charging Voltage	13.6V ≈ 13.8V @25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6V ≈ 14.8V @25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C ≈ 60°C Charge: 0°C ≈ 50°C Storage: -20°C ≈ 60°C
Normal Operating Temperature	25°C ± 5°C
Container Material	A.B.S. UL94-HB, UL94-V0 Optional



LTL series is specially designed for frequent discharge deep cycle application. By using the specially designed active material, strong grids and thick tubular plate construction, the LTL series battery offers reliable performance in high load situations and could provide competitive cycle performance. It is suitable for Electric Vehicle and Golfcart, Floor Machines, Forklifts, Aerial lifts, Robotics, Marine, RV, Mobility and Medical Equipment, and most outdoor application.

DIMENSIONS

AP TERMINAL

Lenght	345mm
Width	175mm
Height	285mm
Total Height	285mm
Terminal	Value
M5	6-7 N°m
M6	8-10 N°m
M8	10-12 N°m

(Note) All of the above information could be changed without prior notice.
IBS Italia reserves the right to explain and update the latest information.

